



ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

DRIVING SURFACE PERFECTION

Date of issue:12/04/2017

Revision date:09/08/2019

Supersedes: 03/05/2019

Version: 3.0

SECTION 1: Identification : Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture
Trade name : ISOPON STONE CHIP PROTECTOR AEROSOL
Product code : SCPB/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED
Unit A, 16 - 20 Cassola Place
Penrith, NSW 2750 - Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.nz - www.u-pol.com.au

Supplier

U-POL NEW ZEALAND LIMITED
c/o Lindsay & Associates
Unit H, 12 Amara Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable aerosols, Category 1 H222
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2A H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
Specific target organ toxicity — Repeated exposure, Category 2 H373

2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) :

Danger

Contains :

acetone (5 - 23 %); xylene (5 - 23 %); reaction mass of ethylbenzene, m-xylene and p-xylene (5 - 23 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe vapours, spray, fume.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear eye protection, protective clothing, protective gloves.
P302+P352 - IF ON SKIN: Wash with plenty of water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

| Name | CAS-No. | % | Classification according to the model Work Health and Safety Regulations (WHS Regulations) |
|---|-----------|---------------|--|
| acetone () | 67-64-1 | 5 - 23 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| xylene () | 1330-20-7 | 5 - 23 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| reaction mass of ethylbenzene, m-xylene and p-xylene () | | 5 - 23 | Flam. Liq. 3, H226 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Other substances (not contributing to the classification of this product) | | 88.73 - 93.23 | |

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Symptoms caused by exposure

| | |
|-------------------------------------|-------------------|
| Symptoms/effects after skin contact | : Irritation. |
| Symptoms/effects after eye contact | : Eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|------------------------------|----------------------------------|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. |
|------------------------------|----------------------------------|

5.2. Special hazards arising from the substance or mixture

| | |
|------------------|---|
| Fire hazard | : Extremely flammable aerosol. |
| Explosion hazard | : Pressurised container: May burst if heated. |
| General measures | : Remove ignition sources. |

5.3. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|----------------------------|
| General measures | : Remove ignition sources. |
|------------------|----------------------------|

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray, vapours, fume. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product. Collect spillage.
Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep cool.
Storage temperature : < 25 °C
Storage area : Store in well ventilated area.
Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

| acetone (67-64-1) | | |
|-------------------|---------------------------|---|
| Australia | Local name | Acetone |
| Australia | TWA (mg/m ³) | 1185 mg/m ³ |
| Australia | TWA (ppm) | 500 ppm |
| Australia | STEL (mg/m ³) | 2375 mg/m ³ |
| Australia | STEL (ppm) | 1000 ppm |
| New Zealand | Local name | Acetone |
| New Zealand | TWA (mg/m ³) | 1185 mg/m ³ |
| New Zealand | TWA (ppm) | 500 ppm |
| New Zealand | STEL (mg/m ³) | 2375 mg/m ³ |
| New Zealand | STEL (ppm) | 1000 ppm |
| New Zealand | Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 9th Edition |

| xylene (1330-20-7) | | |
|--------------------|--------------------------|--|
| New Zealand | Local name | Xylene (Dimethylbenzene) |
| New Zealand | TWA (mg/m ³) | 217 mg/m ³ |
| New Zealand | TWA (ppm) | 50 ppm |
| New Zealand | New Zealand - BEI | 1.5 g/l Parameter: Methylhippuric acid - Medium: Urine - Sampling time: End of shift |
| New Zealand | Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 10th Edition |

Exposure limit values for the other components

8.2. Monitoring

No additional information available

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Materials for protective clothing : Impermeable clothing
Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. [In case of inadequate ventilation] wear respiratory protection.
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance :
Aerosol.
Colour : No data available
Odour : No data available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point / Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative density : No data available
Density : Density : 0.969 g/cm³
Solubility : insoluble in water. soluble in most organic solvents.
Log Pow : No data available
Viscosity, dynamic : ≈
Explosive properties : Pressurised container: May burst if heated.
Explosive limits : No data available
Minimum ignition energy : No data available
VOC content : 578 g/l
VOC content - Regulatory : No data available
Gas group : Press. Gas (Liq.)

SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated. Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

acetone (67-64-1)

LD50 oral rat : 5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| acetone (67-64-1) | |
|---|---|
| LD50 dermal rabbit | 20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal) |
| LC50 inhalation rat (mg/l) | 76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours)) |
| xylene (1330-20-7) | |
| LD50 oral rat | 3523 mg/kg bodyweight (Equivalent or similar to EU Method B.1: Acute Toxicity (Oral), Rat, Male, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rat | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days) |
| LC50 inhalation rat (ppm) | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male) |
| reaction mass of ethylbenzene, m-xylene and p-xylene | |
| LD50 oral rat | 3523 mg/kg (EU Method B.1 (Acute Toxicity (Oral)), rat, male) |
| LD50 dermal rabbit | 12126 mg/kg (Weight of evidence, New Zealand White) |
| LC50 inhalation rat (ppm) | 6350 ppm/4h (4 h, EU Method B.2 (Acute Toxicity (Inhalation)), rat, male, Inhalation, vapours) |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause respiratory irritation. |
| STOT-repeated exposure | : May cause damage to organs through prolonged or repeated exposure. |

| reaction mass of ethylbenzene, m-xylene and p-xylene | |
|---|---|
| NOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight/day (OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), female) |

Aspiration hazard : Not classified

| ISOPON STONE CHIP PROTECTOR AEROSOL | |
|--|---------|
| Vaporizer | Aerosol |

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

| | |
|--------------------------|---|
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Acute aquatic toxicity | : Not classified |
| Chronic aquatic toxicity | : Not classified |

| acetone (67-64-1) | |
|---|--|
| LC50 fish 1 | 5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration) |
| BCF fish 1 | 0.69 (Pisces) |
| BCF other aquatic organisms 1 | 3 (BCFWIN, Calculated value) |
| Log Pow | -0.24 (Test data) |
| xylene (1330-20-7) | |
| LC50 fish 1 | 2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal) |
| ErC50 (algae) | 4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |
| BCF fish 1 | 7.2 - 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across) |
| Log Pow | 3.2 (Read-across, 20 °C) |
| Log Koc | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across) |
| reaction mass of ethylbenzene, m-xylene and p-xylene | |
| LC50 fish 1 | 3300 - 4093 µg/l |
| EC50 Daphnia 1 | 2930 - 4000 µg/l |

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.2. Persistence and degradability

| acetone (67-64-1) | |
|---------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.43 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 1.92 g O ₂ /g substance |
| ThOD | 2.2 g O ₂ /g substance |
| BOD (% of ThOD) | 0.872 (20 day(s), Literature study) |

| xylene (1330-20-7) | |
|-------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |

12.3. Bioaccumulative potential

| acetone (67-64-1) | |
|-------------------------------|-----------------------------------|
| BCF fish 1 | See section 12.1 on ecotoxicology |
| BCF other aquatic organisms 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Not bioaccumulative. |

| xylene (1330-20-7) | |
|---------------------------|--|
| BCF fish 1 | See section 12.1 on ecotoxicology |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| acetone (67-64-1) | |
|--------------------------|---|
| Surface tension | 0.0237 N/m |
| Log Pow | See section 12.1 on ecotoxicology |
| Ecology - soil | No (test)data on mobility of the substance available. |

| xylene (1330-20-7) | |
|---------------------------|---|
| Surface tension | 28.01 - 29.76 mN/m (25 °C) |
| Log Pow | See section 12.1 on ecotoxicology |
| Log Koc | See section 12.1 on ecotoxicology |
| Ecology - soil | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation. |

12.5. Other adverse effects

| | |
|-----------------------|---------------------------------------|
| Ozone | : Not classified |
| Other adverse effects | : No additional information available |

| ISOPON STONE CHIP PROTECTOR AEROSOL | |
|--|-------|
| Fluorinated greenhouse gases | False |

| acetone (67-64-1) | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |

| xylene (1330-20-7) | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |

| reaction mass of ethylbenzene, m-xylene and p-xylene | |
|---|-------|
| Fluorinated greenhouse gases | False |

SECTION 13: Disposal considerations

| | |
|------------------------------|---|
| Regional legislation (waste) | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |

SECTION 14: Transport information

| 14.1. UN number | |
|------------------------|--------|
| UN-No. (ADG) | : 1950 |
| UN-No. (IMDG) | : 1950 |
| UN-No. (IATA) | : 1950 |

| 14.2. Proper Shipping Name - Addition | |
|--|------------|
| Proper Shipping Name (ADG) | : AEROSOLS |
| Proper Shipping Name (IMDG) | : AEROSOLS |

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Proper Shipping Name (IATA) : Aerosols, flammable

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1

Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1

Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1

Hazard labels (IATA) : 2.1



14.4. Packing group

Packing group (ADG) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available

Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950

Special provision (ADG) : 63, 190, 277, 327, 344

Limited quantities (ADG) : See SP 277

Packing instructions (ADG) : P207, LP02

Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP02

Special packing provisions (IMDG) : PP87, L2

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None

Air transport

UN-No. (IATA) : 1950
PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A145, A167, A802
ERG code (IATA) : 10L

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Covered by The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) : This chemical is covered by the Standard for the Uniform Scheduling of Medicines and Poisons

Relevant Poisons Schedule number : Schedule 5

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515

Group standard : Aerosols

ethylbenzene (100-41-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001151

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 09/08/2019

Classification:

| | |
|-----------------|------|
| Flam. Aerosol 1 | H222 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2A | H319 |
| STOT SE 3 | H335 |
| STOT RE 2 | H373 |

Full text of H-statements:

| | |
|---------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 5 (Oral) | Acute toxicity (oral), Category 5 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Aerosol 1 | Flammable aerosols, Category 1 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity — Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H222 | Extremely flammable aerosol. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |

ISOPON STONE CHIP PROTECTOR AEROSOL

Safety Data Sheet

according to the Model Work Health and Safety Regulations

| | |
|------|--|
| H303 | May be harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

SDS Australia U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.