



DRIVING SURFACE PERFECTION

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations  
Issue date: 4/05/2017 Revision date: 20/12/2021 Supersedes: 19/04/2021 Version: 4.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL  
Product code : TRIMMB/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
55 Leland Street  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.com.au](mailto:info@u-pol.com.au) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL New Zealand Limited Ltd  
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki  
Manukau City Auckland 2013  
New Zealand  
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

|  |           |
|--|-----------|
| Aerosol, Category 1  | H222;H229 |
| Serious eye damage/eye irritation, Category 2A                         | H319      |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336      |

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation mark

Signal word (GHS AU) :

Danger

Contains :

acetone (10 – 30 %); methyl acetate (10 – 30 %); n-butyl acetate (< 10 %); ethyl methyl ketone (< 10 %); hydrocarbons, C9, aromatics (< 10 %); cyclohexanone (< 10 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

- P261 - Avoid breathing vapours, fume, spray.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, face protection, protective gloves.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
- Unknown acute toxicity (GHS AU) : 15% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

| Name  | CAS-No.  | %       | Classification according to the model Work Health and Safety Regulations (WHS Regulations)   |
|---|----------|---------|--|
| acetone   | 67-64-1  | 10 – 30 | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336   |
| methyl acetate  | 79-20-9  | 10 – 30 | Flam. Liq. 2, H225<br>Eye Irrit. 2A, H319<br>STOT SE 3, H336   |
| cyclohexanone   | 108-94-1 | < 10    | Flam. Liq. 3, H226<br>Acute Tox. 4 (Oral), H302<br>Acute Tox. 4 (Dermal), H312<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318 |
| Other substances (not contributing to the classification of this product) | -        | 68.66   | -  |

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

- Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Medical attention and special treatment

- Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and materials for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls and personal protection

### 8.1. Control parameters - exposure standards

| acetone (67-64-1)                        |                        |
|--|------------------------|
| Australia - Occupational Exposure Limits |                        |
| Local name                               | Acetone                |
| OES TWA [1]                              | 1185 mg/m <sup>3</sup> |
| OES TWA [2]                              | 500 ppm                |
| OES STEL                                 | 2375 mg/m <sup>3</sup> |
| OES STEL [ppm]                           | 1000 ppm               |

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| acetone (67-64-1)                                 |  |
|---|--|
| Regulatory reference                              | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b> |  |
| Local name  | Acetone  |
| WES-TWA (OEL TWA) [1]                             | 1185 mg/m <sup>3</sup>   |
| WES-TWA (OEL TWA) [2]                             | 500 ppm  |
| WES-STEL (OEL STEL)                               | 2375 mg/m <sup>3</sup>   |
| WES-STEL (OEL STEL) [ppm]                         | 1000 ppm   |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| <b>New Zealand - Biological Exposure Indices</b>  |  |
| Local name  | Acetone  |
| BEI   | 50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift   |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| methyl acetate (79-20-9)                          |  |
| <b>Australia - Occupational Exposure Limits</b>   |  |
| Local name  | Methyl acetate   |
| OES TWA [1]                                       | 606 mg/m <sup>3</sup>  |
| OES TWA [2]                                       | 200 ppm  |
| OES STEL  | 757 mg/m <sup>3</sup>  |
| OES STEL [ppm]                                    | 250 ppm  |
| Regulatory reference                              | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b> |  |
| Local name  | Methyl acetate   |
| WES-TWA (OEL TWA) [1]                             | 606 mg/m <sup>3</sup>  |
| WES-TWA (OEL TWA) [2]                             | 200 ppm  |
| WES-STEL (OEL STEL)                               | 757 mg/m <sup>3</sup>  |
| WES-STEL (OEL STEL) [ppm]                         | 250 ppm  |
| Regulatory reference                              | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| cyclohexanone (108-94-1)                          |  |
| <b>Australia - Occupational Exposure Limits</b>   |  |
| Local name  | Cyclohexanone (Anone)  |
| OES TWA [1]                                       | 100 mg/m <sup>3</sup>  |
| OES TWA [2]                                       | 25 ppm   |
| Remark (AU)                                       | Sk - Absorption through the skin may be a significant source of exposure.  |
| Regulatory reference                              | Workplace exposure standards for airborne contaminants (2019)              |
| <b>New Zealand - Occupational Exposure Limits</b> |  |
| Local name  | Cyclohexanone  |
| WES-TWA (OEL TWA) [1]                             | 100 mg/m <sup>3</sup>  |
| WES-TWA (OEL TWA) [2]                             | 25 ppm   |
| Remark (NZ)                                       | skin (Skin absorption)   |

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### cyclohexanone (108-94-1)

Regulatory reference

Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance : Aerosol.  
Colour : Black  
Odour : Odour threshold is subjective and inadequate to warn for overexposure. Mixture contains one or more component(s) which have the following odour: Odourless Commercial/unpurified substance: unpleasant odour Aromatic odour Sweet odour Fruity odour Mild odour Ether-like odour Almost odourless Pleasant odour Petroleum-like odour Acetone odour Peppermint odour  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Flammability : No data available  
Vapour pressure : No data available  
Relative density : No data available  
Density : Density: 0.732 g/cm<sup>3</sup>  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Explosive properties : Pressurised container: May burst if heated.  
Explosive limits : No data available  
Minimum ignition energy : No data available  
VOC content : 650 g/l  
VOC content - Regulatory : No data available  
Percent Solids : 10.33 wt%

## SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

|                                  |  |
|----------------------------------|--|
| Conditions to avoid              | : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.      |
| Incompatible materials           | : No additional information available  |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

### SECTION 11: Toxicological information

|                             |                  |
|-----------------------------|------------------|
| Acute toxicity (oral)       | : Not classified |
| Acute toxicity (dermal)     | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| acetone (67-64-1)     |  |
|-----------------------|--|
| LD50 oral rat         | 5800 mg/kg bodyweight Animal: rat, Animal sex: female                                |
| LD50 dermal rabbit    | > 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | 76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4                     |
| ATE AU (oral)         | 5800 mg/kg bodyweight  |

| methyl acetate (79-20-9) |  |
|--------------------------|--|
| LD50 oral rat            | 6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)                                       |
| LD50 dermal rat          | > 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity) |
| LC50 Inhalation - Rat    | 49 mg/l  |
| ATE AU (oral)            | 6482 mg/kg bodyweight  |
| ATE AU (dust,mist)       | 49 mg/l/4h   |

| cyclohexanone (108-94-1)        |   |
|---------------------------------|---|
| LD50 oral rat                   | 1890 – 2650 mg/kg bodyweight (BASF test, Rat, Experimental value, Oral, 7 day(s)) |
| LD50 oral                       | 1620 mg/kg  |
| LD50 dermal rabbit              | 1100 mg/kg (BRENNTAG test)  |
| LC50 Inhalation - Rat           | > 6.2 mg/l air Animal: rat  |
| LC50 Inhalation - Rat (Vapours) | 8000 mg/l/4h  |
| ATE AU (oral)                   | 1890 mg/kg bodyweight   |
| ATE AU (dermal)                 | 1100 mg/kg bodyweight   |
| ATE AU (gases)                  | 4500 ppmv/4h  |
| ATE AU (vapours)                | 11 mg/l/4h  |
| ATE AU (dust,mist)              | 1.5 mg/l/4h   |

|                                   |   |
|-----------------------------------|---|
| Unknown acute toxicity (GHS AU)   | : 15% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours)) |
| Skin corrosion/irritation         | : Not classified  |
| Serious eye damage/irritation     | : Causes serious eye irritation.  |
| Respiratory or skin sensitisation | : Not classified  |
| Germ cell mutagenicity            | : Not classified  |
| Carcinogenicity                   | : Not classified  |
| Reproductive toxicity             | : Not classified  |
| STOT-single exposure              | : May cause drowsiness or dizziness.  |

| acetone (67-64-1)    |                                    |
|----------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| <b>methyl acetate (79-20-9)</b>                       |   |
|---|---|
| STOT-single exposure                                  | May cause drowsiness or dizziness.  |
| STOT-repeated exposure                                | : Not classified  |
| <b>methyl acetate (79-20-9)</b>                       |   |
| LOAEC (inhalation, rat, vapour, 90 days)              | 2000 mg/l   |
| NOAEC (inhalation, rat, vapour, 90 days)              | 1057 mg/m <sup>3</sup>  |
| <b>cyclohexanone (108-94-1)</b>                       |   |
| NOAEL (oral, rat, 90 days)                            | 143 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| Aspiration hazard                                     | : Not classified  |
| <b>TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL</b> |   |
| Vaporizer   | Aerosol   |

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

|   |   |
|---|---|
| Ecology - general   | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute)  | : Not classified  |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified  |

| <b>acetone (67-64-1)</b>                                   |  |
|--|--|
| LC50 - Fish [1]  | 6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)                      |
| LOEC (chronic)   | > 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'   |
| NOEC (chronic)   | ≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'   |
| BCF - Fish [1]   | 0.69 (Pisces, Literature study)  |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)   |
| <b>methyl acetate (79-20-9)</b>                            |  |
| LC50 - Fish [1]  | 250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)  |
| EC50 - Crustacea [1]                                       | 1026.7 mg/l Test organisms (species): Daphnia magna  |
| BCF - Fish [1]   | < 1 (Pisces, Literature study)   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| <b>cyclohexanone (108-94-1)</b>                            |  |
| LC50 - Fish [1]  | 527 – 732 mg/l Test organisms (species): Pimephales promelas   |
| EC50 - Crustacea [1]                                       | > 100 mg/l Test organisms (species): Daphnia magna   |

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| cyclohexanone (108-94-1)                                   |  |
|--|--|
| ErC50 algae  | > 100 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP) |
| Partition coefficient n-octanol/water (Log Pow)            | 0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)                          |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)   |

### 12.2. Persistence and degradability

| acetone (67-64-1)               |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.43 g O <sub>2</sub> /g substance   |
| Chemical oxygen demand (COD)    | 1.92 g O <sub>2</sub> /g substance   |
| ThOD                            | 2.2 g O <sub>2</sub> /g substance  |

| methyl acetate (79-20-9)      |                                 |
|-------------------------------|---------------------------------|
| Persistence and degradability | Readily biodegradable in water. |

| cyclohexanone (108-94-1)        |  |
|---------------------------------|--|
| Persistence and degradability   | Biodegradable in the soil. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 1.232 g O <sub>2</sub> /g substance                        |
| Chemical oxygen demand (COD)    | 2.605 g O <sub>2</sub> /g substance                        |
| ThOD                            | 2.605 g O <sub>2</sub> /g substance                        |

### 12.3. Bioaccumulative potential

| acetone (67-64-1)  |  |
|--|--|
| BCF - Fish [1]   | 0.69 (Pisces, Literature study)                              |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (BCF < 500).               |

| methyl acetate (79-20-9)                                   |  |
|--|--|
| BCF - Fish [1]   | < 1 (Pisces, Literature study)   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (Log Kow < 4).   |

| cyclohexanone (108-94-1)                                   |   |
|--|---|
| Partition coefficient n-octanol/water (Log Pow)            | 0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)  |
| Bioaccumulative potential                                  | Low potential for bioaccumulation (Log Kow < 4).  |



# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 12.4. Mobility in soil

#### acetone (67-64-1)

|  |  |
|--|--|
| Surface tension  | 23.3 mN/m (20 °C)  |
| Partition coefficient n-octanol/water (Log Pow)            | -0.23 (Test data)  |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil   | Highly mobile in soil.   |

#### methyl acetate (79-20-9)

|  |  |
|--|--|
| Surface tension  | 24 mN/m (20 °C)  |
| Partition coefficient n-octanol/water (Log Pow)            | 0.18 (Experimental value, 20 °C)   |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP) |
| Ecology - soil   | Highly mobile in soil.   |

#### cyclohexanone (108-94-1)

|  |   |
|--|---|
| Surface tension  | No data available in the literature   |
| Partition coefficient n-octanol/water (Log Pow)            | 0.86 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 1.18 (log Koc, SRC PCKOCWIN v1.66, Calculated value)                  |
| Ecology - soil   | Highly mobile in soil.  |

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

#### TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### acetone (67-64-1)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### methyl acetate (79-20-9)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

#### cyclohexanone (108-94-1)

|                              |       |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |
|------------------------------|-------|

## SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1



### 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

|                                   |   |
|-----------------------------------|---|
| Packing instructions (IMDG)       | : P207, LP200   |
| Special packing provisions (IMDG) | : PP87, L2  |
| EmS-No. (Fire)                    | : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES                             |
| EmS-No. (Spillage)                | : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) |
| Stowage category (IMDG)           | : None  |

### Air transport

|  |                    |
|--|--------------------|
| UN-No. (IATA)                                | : 1950             |
| PCA Excepted quantities (IATA)               | : E0               |
| PCA Limited quantities (IATA)                | : Y203             |
| PCA limited quantity max net quantity (IATA) | : 30kgG            |
| PCA packing instructions (IATA)              | : 203              |
| PCA max net quantity (IATA)                  | : 75kg             |
| CAO packing instructions (IATA)              | : 203              |
| CAO max net quantity (IATA)                  | : 150kg            |
| Special provisions (IATA)                    | : A145, A167, A802 |
| ERG code (IATA)                              | : 10L              |

### 14.8. Hazchem or Emergency Action Code

|              |                  |
|--------------|------------------|
| Hazchem Code | : Not applicable |
|--------------|------------------|

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

#### Hazardous Substances and New Organisms Act

|                      |             |
|----------------------|-------------|
| HSNO Approval Number | : HSR002515 |
| Group standard       | : Aerosols  |

#### LPG, liquefied, under pressure (68476-85-7)

##### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001009 |
|----------------------|-----------|

#### acetone (67-64-1)

##### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001070 |
|----------------------|-----------|

#### methyl acetate (79-20-9)

##### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001188 |
|----------------------|-----------|

#### hydrocarbons, C9, aromatics (64742-95-6)

##### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001503 |
|----------------------|-----------|

#### cyclohexanone (108-94-1)

##### Hazardous Substances and New Organisms Act

|                      |           |
|----------------------|-----------|
| HSNO Approval Number | HSR001112 |
|----------------------|-----------|

### 15.2. International agreements

No additional information available

# TRIM #11 MATT BLACK HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 16: Other information

Revision date : 20/12/2021

| Classification |           |
|----------------|-----------|
| Aerosol 1      | H222;H229 |
| Eye Irrit. 2A  | H319      |
| STOT SE 3      | H336      |

| Full text of H-statements |  |
|---------------------------|--|
| Acute Tox. 4 (Dermal)     | Acute toxicity (dermal), Category 4                                    |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4                                    |
| Acute Tox. 4 (Oral)       | Acute toxicity (oral), Category 4                                      |
| Aerosol 1                 | Aerosol, Category 1  |
| Eye Dam. 1                | Serious eye damage/eye irritation, Category 1                          |
| Eye Irrit. 2A             | Serious eye damage/eye irritation, Category 2A                         |
| Flam. Liq. 2              | Flammable liquids, Category 2  |
| Flam. Liq. 3              | Flammable liquids, Category 3  |
| Skin Irrit. 2             | Skin corrosion/irritation, Category 2                                  |
| STOT SE 3                 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |
| H225                      | Highly flammable liquid and vapour                                     |
| H226                      | Flammable liquid and vapour  |
| H302                      | Harmful if swallowed   |
| H312                      | Harmful in contact with skin   |
| H315                      | Causes skin irritation   |
| H318                      | Causes serious eye damage  |
| H319                      | Causes serious eye irritation  |
| H332                      | Harmful if inhaled   |
| H336                      | May cause drowsiness or dizziness                                      |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).