



DRIVING SURFACE PERFECTION

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations  
Issue date: 20/01/2023 Version: 1.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : RAPTOR ENGINE ENAMEL SATIN BLACK  
Product code : REESB/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coatings and paints, thinners, paint removers

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
55 Leland Street  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.com.au](mailto:info@u-pol.com.au) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Signal word (GHS AU) : Danger

Contains : methyl acetate (30 – 60 %); n-butyl acetate (< 10 %)

Hazard statements (GHS AU) : H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P251 - Do not pierce or burn, even after use.  
P261 - Avoid breathing fume, spray, vapours.  
P264 - Wash hands thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Unknown acute toxicity (GHS AU) : 38.63% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
methyl acetate	79-20-9	30 – 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Other substances (not contributing to the classification of this product)	-	61.37	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

methyl acetate (79-20-9)	
<b>Australia - Occupational Exposure Limits</b>	
Local name	Methyl acetate
OES TWA [1]	606 mg/m <sup>3</sup>
OES TWA [2]	200 ppm
OES STEL	757 mg/m <sup>3</sup>
OES STEL [ppm]	250 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
<b>New Zealand - Occupational Exposure Limits</b>	
Local name	Methyl acetate
WES-TWA (OEL TWA) [1]	606 mg/m <sup>3</sup>
WES-TWA (OEL TWA) [2]	200 ppm
WES-STEL (OEL STEL)	757 mg/m <sup>3</sup>
WES-STEL (OEL STEL) [ppm]	250 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 8.2. Biological Monitoring

No additional information available

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Colour : Black  
Odour : characteristic  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : No data available  
Boiling point : 57 °C  
Flash point : -13  
Auto-ignition temperature : No data available  
Flammability : No data available  
Vapour pressure : No data available  
Relative density : No data available  
Density : Density: 0.812 g/cm<sup>3</sup>  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Explosive properties : Pressurised container: May burst if heated.  
Explosive limits : No data available  
Minimum ignition energy : No data available  
VOC content : 660 g/l  
VOC content - Regulatory : No data available

## SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.  
Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.  
Incompatible materials : No additional information available  
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	49 mg/l
ATE AU (oral)	6482 mg/kg bodyweight
ATE AU (dust,mist)	49 mg/l/4h

Unknown acute toxicity (GHS AU) : 38.63% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : May cause drowsiness or dizziness.

methyl acetate (79-20-9)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

methyl acetate (79-20-9)	
LOAEC (inhalation, rat, vapour, 90 days)	2000 mg/l
NOAEC (inhalation, rat, vapour, 90 days)	1057 mg/m <sup>3</sup>

Aspiration hazard : Not classified

RAPTOR ENGINE ENAMEL SATIN BLACK	
Vaporizer	Aerosol

## SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

### 12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

methyl acetate (79-20-9)	
LC50 - Fish [1]	250 – 350 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	1026.7 mg/l Test organisms (species): Daphnia magna
BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 12.2. Persistence and degradability

#### methyl acetate (79-20-9)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

### 12.3. Bioaccumulative potential

#### methyl acetate (79-20-9)

BCF - Fish [1]	< 1 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

#### methyl acetate (79-20-9)

Surface tension	24 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Pow)	0.18 (Experimental value, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

#### RAPTOR ENGINE ENAMEL SATIN BLACK

Fluorinated greenhouse gases	False
------------------------------	-------

#### methyl acetate (79-20-9)

Fluorinated greenhouse gases	False
------------------------------	-------

## SECTION 13: Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1



### 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344, 381  
Limited quantities (ADG) : See SP 277  
Excepted quantities (ADG) : E0  
Packing instructions (ADG) : P207, LP200  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None

# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Xylene (1330-20-7)	
<b>Hazardous Substances and New Organisms Act</b>	
HSNO Approval Number	HSR000983

methyl acetate (79-20-9)	
<b>Hazardous Substances and New Organisms Act</b>	
HSNO Approval Number	HSR001188

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Classification	
Aerosol 1	H222;H229
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements	
Aerosol 1	Aerosol, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness



# RAPTOR ENGINE ENAMEL SATIN BLACK

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

---

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).