



DRIVING SURFACE PERFECTION

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations  
Issue date: 4/05/2017 Revision date: 20/12/2021 Supersedes: 19/04/2021 Version: 3.0

### SECTION 1: Product identifier

#### 1.1. GHS Product identifier

Product form : Mixture  
Trade name : TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL  
Product code : TRIMSLW/AL

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

#### 1.4. Details of manufacturer or importer

##### Supplier

U-POL Australia Pty Limited Ltd  
55 Leland Street  
Penrith NSW 2750  
Australia  
T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.com.au](mailto:info@u-pol.com.au) - [www.u-pol.com](http://www.u-pol.com)

##### Supplier

U-POL New Zealand Limited Ltd  
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki  
Manukau City Auckland 2013  
New Zealand  
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)

#### 1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

### SECTION 2: Hazard identification

#### 2.1. Classification of the hazardous chemical

##### Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

#### 2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation  
mark

Signal word (GHS AU) :

Danger

Contains :

acetone (10 – 30 %); n-butyl acetate (< 10 %); 4-methylpentan-2-one; isobutyl methyl ketone (< 10 %); naphtha (petroleum), hydrotreated heavy (< 10 %); hydrocarbons, C9, aromatics (< 10 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Precautionary statements (GHS AU) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P103 - Read carefully and follow all instructions.  
P261 - Avoid breathing fume, spray, vapours.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear eye protection, face protection, protective gloves.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.  
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

## SECTION 3: Composition and information on ingredients

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone	67-64-1	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
4-methylpentan-2-one; isobutyl methyl ketone	108-10-1	< 10	Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Other substances (not contributing to the classification of this product)	-	72.03	-

## SECTION 4: First aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center or a doctor if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : Irritation.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Medical attention and special treatment

Other medical advice or treatment : Treat symptomatically.

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and materials for containment and cleaning up

For containment : Contain released product. Collect spillage.  
Methods for cleaning up : Mechanically recover the product.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.  
Storage temperature : < 25 °C  
Special rules on packaging : Keep only in original container.

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters - exposure standards

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

<b>acetone (67-64-1)</b>	
<b>Australia - Occupational Exposure Limits</b>	
Local name	Acetone
OES TWA [1]	1185 mg/m <sup>3</sup>
OES TWA [2]	500 ppm
OES STEL	2375 mg/m <sup>3</sup>
OES STEL [ppm]	1000 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
<b>New Zealand - Occupational Exposure Limits</b>	
Local name	Acetone
WES-TWA (OEL TWA) [1]	1185 mg/m <sup>3</sup>
WES-TWA (OEL TWA) [2]	500 ppm
WES-STEEL (OEL STEL)	2375 mg/m <sup>3</sup>
WES-STEEL (OEL STEL) [ppm]	1000 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
<b>New Zealand - Biological Exposure Indices</b>	
Local name	Acetone
BEI	50 mg/l Parameter: Acetone - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
<b>4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)</b>	
<b>Australia - Occupational Exposure Limits</b>	
Local name	Methyl isobutyl ketone (MIBK; 4-Methyl-2-pentanone; Hexone)
OES TWA [1]	205 mg/m <sup>3</sup>
OES TWA [2]	50 ppm
OES STEL	307 mg/m <sup>3</sup>
OES STEL [ppm]	75 ppm
Regulatory reference	Workplace exposure standards for airborne contaminants (2019)
<b>New Zealand - Occupational Exposure Limits</b>	
Local name	Methyl isobutyl ketone (Hexone)
WES-TWA (OEL TWA) [1]	205 mg/m <sup>3</sup>
WES-TWA (OEL TWA) [2]	50 ppm
WES-STEEL (OEL STEL)	307 mg/m <sup>3</sup>
WES-STEEL (OEL STEL) [ppm]	75 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition
<b>New Zealand - Biological Exposure Indices</b>	
Local name	Methyl isobutyl ketone (MIBK)
BEI	0.7 mg/l Parameter: MIBK - Medium: Urine - Sampling time: End of shift
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 12th Edition

### 8.2. Biological Monitoring

No additional information available

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

### 8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Gloves. Protective clothing. Safety glasses.  
Materials for protective clothing : Impermeable clothing  
Hand protection : Protective gloves  
Eye protection : Safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

Physical state : Liquid  
Appearance : Aerosol.  
Colour : Silver  
Odour : Odour threshold is subjective and inadequate to warn for overexposure.  
Mixture contains one or more component(s) which have the following odour:  
Aromatic odour Sweet odour Fruity odour Odourless Irritating/pungent odour Alcohol odour  
Mild odour Ether-like odour Pleasant odour Camphor odour Almost odourless Petroleum-like odour  
Odour threshold : No data available  
pH : No data available  
Relative evaporation rate (butylacetate=1) : No data available  
Melting point / Freezing point : No data available  
Boiling point : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Flammability : No data available  
Vapour pressure : No data available  
Relative density : No data available  
Density : Density: 0.764 g/cm<sup>3</sup>  
Solubility : insoluble in water. soluble in most organic solvents.  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Explosive properties : Pressurised container: May burst if heated.  
Explosive limits : No data available  
Minimum ignition energy : No data available  
VOC content : 650 g/l  
VOC content - Regulatory : No data available  
Gas group : Press. Gas (Liq.)  
Percent Solids : 6.83 wt%

## SECTION 10: Stability and reactivity

Reactivity : Extremely flammable aerosol. Pressurised container: May burst if heated.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.  
Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.  
Incompatible materials : No additional information available  
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15800 mg/kg bodyweight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE AU (oral)	5800 mg/kg bodyweight

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
LD50 oral rat	2080 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1,91 - 2,27
LD50 dermal rat	≥ 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat (Vapours)	10 – 20 mg/l/4h
ATE AU (oral)	2080 mg/kg bodyweight
ATE AU (gases)	4500 ppmv/4h
ATE AU (vapours)	10 mg/l/4h
ATE AU (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	: Not classified
------------------------	------------------

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

Aspiration hazard	: Not classified
-------------------	------------------

TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL	
Vaporizer	Aerosol

### SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

#### acetone (67-64-1)

LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

LC50 - Fish [1]	> 179 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	> 200 mg/l Test organisms (species): Daphnia magna
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)

### 12.2. Persistence and degradability

#### acetone (67-64-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	1.92 g O <sub>2</sub> /g substance
ThOD	2.2 g O <sub>2</sub> /g substance

#### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.06 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.16 g O <sub>2</sub> /g substance
ThOD	2.72 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

#### acetone (67-64-1)

BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.008 (log Koc, Weight of evidence, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	1.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	See section 12.1 on ecotoxicology 2.008 (log Koc, Weight of evidence, Calculated value)
Ecology - soil	Low potential for adsorption in soil.

### 12.5. Other adverse effects

Ozone : Not classified  
Other adverse effects : No additional information available

TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL	
Fluorinated greenhouse gases	False

acetone (67-64-1)	
Fluorinated greenhouse gases	False

4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)	
Fluorinated greenhouse gases	False

## SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### 14.1. UN number

UN-No. (ADG) : 1950  
UN-No. (IMDG) : 1950  
UN-No. (IATA) : 1950

### 14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS  
Proper Shipping Name (IMDG) : AEROSOLS  
Proper Shipping Name (IATA) : Aerosols, flammable



# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### 14.3. Transport hazard class(es)

#### ADG

Transport hazard class(es) (ADG) : 2.1  
Danger labels (ADG) : 2.1  
:



#### IMDG

Transport hazard class(es) (IMDG) : 2.1  
Danger labels (IMDG) : 2.1  
:



#### IATA

Transport hazard class(es) (IATA) : 2.1  
Danger labels (IATA) : 2.1  
:



### 14.4. Packing group

Packing group (ADG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Marine pollutant : No  
Dangerous for the environment : No  
Other information : No supplementary information available

### 14.6. Special precautions for user

Specific storage requirement : No data available  
Shock sensitivity : No data available

### 14.7. Additional information

Other information : No supplementary information available

#### Transport by road and rail

UN-No. (ADG) : 1950  
Special provision (ADG) : 63, 190, 277, 327, 344  
Limited quantities (ADG) : See SP 277  
Packing instructions (ADG) : P207, LP02  
Special packing provisions (ADG) : PP87, L2

#### Transport by sea

UN-No. (IMDG) : 1950  
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES  
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)  
Stowage category (IMDG) : None

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### Air transport

UN-No. (IATA)	: 1950
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### 14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

#### Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515  
Group standard : Aerosols

#### acetone (67-64-1)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001070
----------------------	-----------

#### solvent naphtha (petroleum), light aromatic (64742-95-6)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001503
----------------------	-----------

#### aluminium powder (stabilised) (7429-90-5)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001263(coated, PGII) HSR001471(coated, PGIII) HSR001472(uncoated, PGII) HSR001473(coated, PGIII) HSR001474 pyrophoric
----------------------	--

#### 1-butanol (71-36-3)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001096
----------------------	-----------

#### 2-methoxy-1-methylethyl acetate (108-65-6)

##### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001219
----------------------	-----------

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### phosphoric acid ... %, orthophosphoric acid ... % (7664-38-2)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001545(dilution) HSR001571(dilution)
----------------------	--

### n-butyl acetate (123-86-4)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001091
----------------------	-----------

### 4-methylpentan-2-one; isobutyl methyl ketone (108-10-1)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001194
----------------------	-----------

### toluene (108-88-3)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001227
----------------------	-----------

### butyl glycoether (111-76-2)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001154
----------------------	-----------

### 2-phenoxyethanol (122-99-6)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR003045
----------------------	-----------

### dimethyl ether (115-10-6)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000995
----------------------	-----------

### hydrocarbons, C9, aromatics (64742-95-6)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001503
----------------------	-----------

### Xylene (1330-20-7)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000983
----------------------	-----------

### ethylbenzene (100-41-4)

#### Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001151
----------------------	-----------

### 15.2. International agreements

No additional information available

# TRIM #11 SILVER WHEELS HIGH BUILD TOPCOAT AEROSOL

## Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

### SECTION 16: Other information

Revision date : 20/12/2021

Classification	
Aerosol 1	H222;H229
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H336

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aerosol 1	Aerosol, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H303	May be harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).