



DRIVING SURFACE PERFECTION

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Issue date: 29/03/2017 Revision date: 23/11/2021 Supersedes: 3/05/2019 Version: 4.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : ISOPON SCRATCH & STONE CHIP FILLER

1.2. Other means of identification

Other means of identification : Component of: SSCF/PBX

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
55 Leland Street
Penrith NSW 2750
Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki
Manukau City Auckland 2013
New Zealand
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 3 H226

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Signal word (GHS AU) : Warning
Hazard statements (GHS AU) : H226 - Flammable liquid and vapour
Precautionary statements (GHS AU) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read carefully and follow all instructions.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. heat, hot surfaces, open flames, sparks
P233 - Keep container tightly closed.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 3: Composition and information on ingredients

This mixture does not contain any substances to be mentioned according to the applicable regulations

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects after skin contact	: Irritation.
-------------------------------------	---------------

4.3. Medical attention and special treatment

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Hazchem Code	: * 3Y

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed.
- Storage temperature : < 20 °C
- Storage area : Store in well ventilated area.
- Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

No additional information available

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

- Personal protective equipment : Gloves. Safety glasses. Protective clothing.
- Materials for protective clothing : Impermeable clothing
- Hand protection : Protective gloves
- Eye protection : Safety glasses
- Skin and body protection : Wear suitable protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s)



- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Colour : Green
- Odour : characteristic
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Melting point / Freezing point : Melting point: Not applicable
- Boiling point : > 35 °C
- Flash point : 28 °C
- Auto-ignition temperature : No data available

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Flammability	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density: 1.565 (1.55 – 1.58) g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 65495.208 mm ² /s
Viscosity, dynamic	: 102.5 (90 – 115) Pa·s
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
VOC content	: 364 g/l
VOC content - Regulatory	: No data available
Percent Solids	: 0 wt%

SECTION 10: Stability and reactivity

Reactivity	: Flammable liquid and vapour.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Incompatible materials	: No additional information available
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

ISOPON SCRATCH & STONE CHIP FILLER

Viscosity, kinematic	65495.208 mm ² /s
----------------------	------------------------------

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

ISOPON SCRATCH & STONE CHIP FILLER

Fluorinated greenhouse gases	False
------------------------------	-------

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1866
UN-No. (IMDG) : 1866
UN-No. (IATA) : 1866

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : RESIN SOLUTION
Proper Shipping Name (IMDG) : RESIN SOLUTION
Proper Shipping Name (IATA) : Resin solution

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3
Danger labels (ADG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations



14.4. Packing group

Packing group (ADG) : III - Substances presenting low danger
Packing group (IMDG) : III
Packing group (IATA) : III

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1866
Special provision (ADG) : 223
Limited quantities (ADG) : 5I
Packing instructions (ADG) : P001, IBC03, LP01
Special packing provisions (ADG) : PP1
Portable tank and bulk container instructions (ADG) : T2
Portable tank and bulk container special provisions (ADG) : TP1

Transport by sea

UN-No. (IMDG) : 1866
Special provisions (IMDG) : 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

UN-No. (IATA) : 1866
PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y344
PCA limited quantity max net quantity (IATA) : 10L
PCA packing instructions (IATA) : 355
PCA max net quantity (IATA) : 60L
CAO packing instructions (IATA) : 366
CAO max net quantity (IATA) : 220L
Special provisions (IATA) : A3
ERG code (IATA) : 3L

ISOPON SCRATCH & STONE CHIP FILLER

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3Y

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Covered by The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) : This chemical is covered by the Standard for the Uniform Scheduling of Medicines and Poisons
Relevant Poisons Schedule number : Schedule 5

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002662
Group standard : Surface coatings and colourants

n-butyl acetate (123-86-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001091
----------------------	-----------

Xylene (1330-20-7)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000983
----------------------	-----------

ethylbenzene (100-41-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001151
----------------------	-----------

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 23/11/2021

Classification

Flam. Liq. 3	H226
--------------	------

Full text of H-statements

Flam. Liq. 3	Flammable liquids, Category 3
--------------	-------------------------------

H226	Flammable liquid and vapour
------	-----------------------------

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.