



DRIVING SURFACE PERFECTION

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations
Issue date: 8/12/2016 Revision date: 17/12/2021 Supersedes: 19/04/2021 Version: 4.0

SECTION 1: Product identifier

1.1. GHS Product identifier

Product form : Mixture
Trade name : HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL
Product code : HIGHG/AL

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Details of manufacturer or importer

Supplier

U-POL Australia Pty Limited Ltd
55 Leland Street
Penrith NSW 2750
Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.com.au - www.u-pol.com

Supplier

U-POL New Zealand Limited Ltd
c/o Lindsay & Associates Unit H, 12 Amara Place, East Tamaki
Manukau City Auckland 2013
New Zealand
T + 612 4731 2655 / 027 630 3691 - F + 612 4731 2611
info@u-pol.co.nz - www.u-pol.com

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

| | |
|--|-----------|
| Aerosol, Category 1 | H222;H229 |
| Skin corrosion/irritation, Category 2 | H315 |
| Serious eye damage/eye irritation, Category 2A | H319 |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis | H336 |
| Specific target organ toxicity – Repeated exposure, Category 2 | H373 |

2.2. GHS Label elements, including precautionary statements

Hazard pictograms (GHS AU) :



Flame

Exclamation mark

Signal word (GHS AU) :

Danger

Contains :

ethyl methyl ketone (30 – 60 %); Xylene (10 – 30 %)

Hazard statements (GHS AU) :

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| | |
|---------------------------------------|---|
| Precautionary statements (GHS AU) | : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe vapours, spray, fume. P264 - Wash hands thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear eye protection, face protection, protective gloves. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. |
| Additional hazard statements (GHS AU) | : AUH066 - Repeated exposure may cause skin dryness or cracking. |

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

| Name | CAS-No. | % | Classification according to the model Work Health and Safety Regulations (WHS Regulations) |
|---|-----------|---------------|---|
| ethyl methyl ketone | 78-93-3 | 30 – 60 | Flam. Liq. 2, H225 Acute Tox. 5 (Oral), H303 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Xylene | 1330-20-7 | 10 – 30 | Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Other substances (not contributing to the classification of this product) | - | 89.63 – 89.67 | - |

SECTION 4: First aid measures

4.1. Description of necessary first-aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : Call a poison center or a doctor if you feel unwell. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : Rinse eyes with water as a precaution. |
| First-aid measures after ingestion | : Call a poison center or a doctor if you feel unwell. |

4.2. Symptoms caused by exposure

| | |
|-------------------------------------|--------------------------------------|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Irritation. |

4.3. Medical attention and special treatment

| | |
|-----------------------------------|--------------------------|
| Other medical advice or treatment | : Treat symptomatically. |
|-----------------------------------|--------------------------|

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Safety glasses. Gloves.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and materials for containment and cleaning up

For containment : Contain released product. Collect spillage.

Methods for cleaning up : Mechanically recover the product.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing fume, spray, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Storage temperature : < 25 °C

Storage area : Store in well ventilated area.

Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| ethyl methyl ketone (78-93-3) | |
|---|--|
| Australia - Occupational Exposure Limits | |
| Local name | Methyl ethyl ketone (MEK; 2-Butanone) |
| OES TWA [1] | 445 mg/m ³ |
| OES TWA [2] | 150 ppm |
| OES STEL | 890 mg/m ³ |
| OES STEL [ppm] | 300 ppm |
| Regulatory reference | Workplace exposure standards for airborne contaminants (2019) |
| New Zealand - Occupational Exposure Limits | |
| Local name | Methyl ethyl ketone (MEK, 2-Butanone) |
| WES-TWA (OEL TWA) [1] | 445 mg/m ³ |
| WES-TWA (OEL TWA) [2] | 150 ppm |
| WES-STEEL (OEL STEL) | 890 mg/m ³ |
| WES-STEEL (OEL STEL) [ppm] | 300 ppm |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| New Zealand - Biological Exposure Indices | |
| Local name | Methyl ethyl ketone (MEK) |
| BEI | 2 mg/l Parameter: MEK - Medium: Urine - Sampling time: End of shift |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| Xylene (1330-20-7) | |
| New Zealand - Occupational Exposure Limits | |
| Local name | Xylene (Dimethylbenzene) |
| WES-TWA (OEL TWA) [1] | 217 mg/m ³ |
| WES-TWA (OEL TWA) [2] | 50 ppm |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |
| New Zealand - Biological Exposure Indices | |
| Local name | Xylene |
| BEI | 1.5 g/l Parameter: Methylhippuric acid - Medium: Urine - Sampling time: End of shift |
| Regulatory reference | Workplace Exposure Standards and Biological Exposure Indices, 12th Edition |

8.2. Biological Monitoring

No additional information available

8.3. Engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment : Gloves. Protective clothing. Safety glasses.
Materials for protective clothing : Impermeable clothing
Hand protection : Protective gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Personal protective equipment symbol(s)



Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Appearance | : Aerosol. |
| Colour | : Grey |
| Odour | : characteristic |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point / Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Flammability | : No data available |
| Vapour pressure | : No data available |
| Relative density | : No data available |
| Density | : Density: 0.774 g/cm ³ |
| Solubility | : insoluble in water. soluble in most organic solvents. |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Explosive properties | : No data available |
| Explosive limits | : No data available |
| Minimum ignition energy | : No data available |
| VOC content | : 617 g/l |
| VOC content - Regulatory | : No data available |
| Gas group | : Press. Gas (Liq.) |
| Percent Solids | : 20.47 % |

SECTION 10: Stability and reactivity

| | |
|------------------------------------|--|
| Reactivity | : Extremely flammable aerosol. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : No dangerous reactions known under normal conditions of use. |
| Conditions to avoid | : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition. |
| Incompatible materials | : No additional information available |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

SECTION 11: Toxicological information

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| ethyl methyl ketone (78-93-3) | |
|-------------------------------|--|
| LD50 oral rat | 2193 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 8100 mg/kg bw/day (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s)) |
| ATE AU (oral) | 2193 mg/kg bodyweight |

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| Xylene (1330-20-7) | |
|-----------------------------|--|
| LD50 oral rat | > 4000 mg/kg bodyweight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rat | 12126 mg/kg (Non-GLP, read-across from supporting substance, single dermal dose under occlusion followed by observation for 14 days) |
| LD50 dermal rabbit | 12126 mg/kg bodyweight Animal: rabbit, Animal sex: male |
| LC50 Inhalation - Rat | 29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s)) |
| LC50 Inhalation - Rat [ppm] | 6700 ppm/4h (EU Method B.2 (Acute Toxicity (Inhalation)), 4h, rat, male) |
| ATE AU (dermal) | 1100 mg/kg bodyweight |
| ATE AU (gases) | 6700 ppmv/4h |
| ATE AU (vapours) | 11 mg/l/4h |
| ATE AU (dust,mist) | 1.5 mg/l/4h |

| | |
|-----------------------------------|--------------------------------------|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : May cause drowsiness or dizziness. |

| ethyl methyl ketone (78-93-3) | |
|--------------------------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| Xylene (1330-20-7) | |
|---------------------------|-----------------------------------|
| STOT-single exposure | May cause respiratory irritation. |

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

| Xylene (1330-20-7) | |
|----------------------------|---|
| LOAEL (oral, rat, 90 days) | 150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity) |
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : Not classified

| HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL | |
|--|---------|
| Vaporizer | Aerosol |

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

| | |
|---|---|
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

| ethyl methyl ketone (78-93-3) | |
|--------------------------------------|---|
| LC50 - Fish [1] | 2993 mg/l Test organisms (species): Pimephales promelas |

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| ethyl methyl ketone (78-93-3) | |
|--|--|
| EC50 - Crustacea [1] | 308 mg/l Test organisms (species): Daphnia magna |
| ErC50 algae | 1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate) |
| Partition coefficient n-octanol/water (Log Pow) | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |

| Xylene (1330-20-7) | |
|--|--|
| LC50 - Fish [1] | 2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) |
| EC50 - Crustacea [1] | > 3.4 mg/l Test organisms (species): Ceriodaphnia dubia |
| ErC50 algae | 4.36 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |
| NOEC chronic fish | > 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d' |
| BCF - Fish [1] | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across) |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across) |

12.2. Persistence and degradability

| ethyl methyl ketone (78-93-3) | |
|---------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 2.03 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.31 g O ₂ /g substance |
| ThOD | 2.44 g O ₂ /g substance |

| Xylene (1330-20-7) | |
|-------------------------------|--|
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |

12.3. Bioaccumulative potential

| ethyl methyl ketone (78-93-3) | |
|--|---|
| Partition coefficient n-octanol/water (Log Pow) | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

| Xylene (1330-20-7) | |
|--|--|
| BCF - Fish [1] | 7.2 – 25.9 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across) |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across) |

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| Xylene (1330-20-7) | |
|---------------------------|--|
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |

12.4. Mobility in soil

| ethyl methyl ketone (78-93-3) | |
|--|---|
| Surface tension | No data available in the literature |
| Partition coefficient n-octanol/water (Log Pow) | 0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 0.654 – 1.281 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. Slightly harmful to plants. |

| Xylene (1330-20-7) | |
|--|---|
| Surface tension | 28.01 – 29.76 mN/m (25 °C) |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | See section 12.1 on ecotoxicology 2.73 (log Koc, Equivalent or similar to OECD 121, Read-across) |
| Ecology - soil | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation. |

12.5. Other adverse effects

Ozone : Not classified
Other adverse effects : No additional information available

| HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL | |
|---|-------|
| Fluorinated greenhouse gases | False |

| ethyl methyl ketone (78-93-3) | |
|-------------------------------|-------|
| Fluorinated greenhouse gases | False |

| Xylene (1330-20-7) | |
|------------------------------|-------|
| Fluorinated greenhouse gases | False |

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1950
UN-No. (IMDG) : 1950
UN-No. (IATA) : 1950

14.2. UN Proper Shipping Name

Proper Shipping Name (ADG) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS
Proper Shipping Name (IATA) : Aerosols, flammable

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 2.1
Danger labels (ADG) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



14.4. Packing group

Packing group (ADG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1950
Special provision (ADG) : 63, 190, 277, 327, 344
Limited quantities (ADG) : See SP 277
Packing instructions (ADG) : P207, LP02
Special packing provisions (ADG) : PP87, L2

Transport by sea

UN-No. (IMDG) : 1950
Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage) : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG) : None

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

Air transport

| | |
|--|--------------------|
| UN-No. (IATA) | : 1950 |
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provisions (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

14.8. Hazchem or Emergency Action Code

Hazchem Code : Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002515
Group standard : Aerosols

n-butyl acetate (123-86-4)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001091 |
|----------------------|-----------|

LPG, liquefied, under pressure (68476-85-7)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001009 |
|----------------------|-----------|

ethyl methyl ketone (78-93-3)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001190 |
|----------------------|-----------|

carbon black (1333-86-4)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR002801 |
|----------------------|-----------|

2-methoxy-1-methylethyl acetate (108-65-6)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001219 |
|----------------------|-----------|

2,6-dimethylheptan-4-one; di-isobutyl ketone (108-83-8)

Hazardous Substances and New Organisms Act

| | |
|----------------------|-----------|
| HSNO Approval Number | HSR001130 |
|----------------------|-----------|

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| Xylene (1330-20-7) | |
|---|-----------|
| Hazardous Substances and New Organisms Act | |
| HSNO Approval Number | HSR000983 |

| fatty acids, C14-18 and C16-18-unsatd., maleated (85711-46-2) | |
|---|-----------|
| Hazardous Substances and New Organisms Act | |
| HSNO Approval Number | HSR002495 |

| ethylbenzene (100-41-4) | |
|---|-----------|
| Hazardous Substances and New Organisms Act | |
| HSNO Approval Number | HSR001151 |

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 17/12/2021

| Classification | |
|----------------|-----------|
| Aerosol 1 | H222;H229 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2A | H319 |
| STOT SE 3 | H336 |
| STOT RE 2 | H373 |

| Full text of H-statements | |
|---------------------------|--|
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhal.), Category 4 |
| Acute Tox. 5 (Oral) | Acute toxicity (oral), Category 5 |
| Aerosol 1 | Aerosol, Category 1 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| STOT RE 2 | Specific target organ toxicity – Repeated exposure, Category 2 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation |
| H225 | Highly flammable liquid and vapour |
| H226 | Flammable liquid and vapour |
| H303 | May be harmful if swallowed |
| H304 | May be fatal if swallowed and enters airways |

HIGH #5 HIGH BUILD PRIMER FILLER GREY AEROSOL

Safety Data Sheet

according to the Work Health and Safety (WHS) Regulations

| Full text of H-statements | |
|---------------------------|---|
| H312 | Harmful in contact with skin |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H336 | May cause drowsiness or dizziness |
| H373 | May cause damage to organs through prolonged or repeated exposure |

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.