



# BLEND#9

DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

Version: 1.0

Fade Out Reducer Solvent

## DESCRIPTION

BLEND#9 is a specially formulated solvent to assist in dissolving the dry edges of freshly sprayed clearcoats and topcoats

BLEND#9 gives a soft edge to the repair enabling the work efficiency to be increased by limiting the size/scale of the repair to a single panel. Its blending properties enable the job to be confined to a spot repair

- Invisible blend finish
- For use with all coatings
- Suitable for smart repairs

## INSTRUCTIONS FOR USE



### Mixing

Shake the aerosol can for at least 2 minutes before use.

Holding the aerosol approximately 25cm from the panel, apply a light mist coat of BLEND#9 over the bled area of the freshly applied clearcoat or topcoat.

Two rapid passes of the aerosol will give an ideal blending process. The dry edge of the repair area will melt into the surrounding original paintwork, this will minimise the need for further processing once the clearcoat or topcoat has cured.

Once BLEND#9 is applied, follow the clearcoat or topcoat manufacturers instructions for flash off and drying

## STORAGE & VOC INFORMATION



### Shelf Life

2 years subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 5°C - 25°C

Recommended Application Temperature 20°C



### VOC Information

The EU limit for this product (product category: IIB.e) in ready to use form is 840g/litre. The VOC content of this product in ready to use form is 688 g/litre.

Order Code	Format	Colour	VOC g/l
BLEND/AL	450ml Aerosol	Clear	688

**IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.**

**This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.** Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM). U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL AUSTRALIA PTY Ltd  
PO BOX 375  
Springwood NSW 2777  
[WWW.U-POL.COM](http://WWW.U-POL.COM)

Contact Australia  
T: +61 2 4731 2655  
F: +61 2 4731 2611  
[sales@u-pol.com.au](mailto:sales@u-pol.com.au)

U-POL NEW ZEALAND Ltd  
T: +64 27 630 3691  
F: +61 2 4731 2611  
[sales@u-pol.com](mailto:sales@u-pol.com)

Technical  
T: +44 (0)1933 230 310  
F: +44 (0)1933 425 797  
[technicaldepartment@u-pol.com](mailto:technicaldepartment@u-pol.com)