



TRIM#11

DRIVING SURFACE PERFECTION™
TECHNICAL DATA SHEET
Version: 1.0

High Build Topcoat

DESCRIPTION

A high build topcoat to restore the original appearance of trim and area's around windows, doors, handles, outside of mirrors, bumpers and alloy wheels

- Suitable for use over existing paint surfaces
- Fast drying, clog free formulation
- High opacity

TECHNICAL DATA AND APPLICATION GUIDE



Substrates

- Lightly abraded E coat
- Prepared painted surfaces



Tools Required

- SYSTEM 20™ Degreaser
- MAXIMUM Abrasives



Substrate Preparation

For best results, ensure the surface is thoroughly cleaned, degreased, dried and dust free. Abrade primed surfaces wet or dry with 400-600, degrease and dry. For optimum results on bare metal, galvanised steel and aluminium surfaces, apply 1-2 light even coats of ACID#8 Etch-Primer, allowing 10 - 20 minutes drying time before priming.



Mixing

Shake the aerosol can for at least 2 minutes before use.



Coats

1 - 2 coats at a distance of approx. 25 cm from the surface.

Build / microns 15μ

*Theoretical Coverage approx. m²/unit 4.5

**Theoretical Coverage per unit assuming 100% transfer efficiency and giving the dry film thickness between indicated values.*



Flash-off / min @ 20°C

between coats 3 -5 mins



Drying Times

Dust free @ 20°C / min 20 - 30 minutes

STORAGE & VOC INFORMATION

Shelf Life

2 years subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 5°C - 25°C

Recommended Application Temperature 20°C



TRIM#11

DRIVING SURFACE PERFECTION™
TECHNICAL DATA SHEET
Version: 1.0

High Build Topcoat



VOC Information

The EU limit for this product (product category: IIB.e) in ready to use form is 840g/litre. The VOC content of this product in ready to use form is as per the table below.

Order Code	Format	Colour	VOC g/l
TRIMGB/AL	450ml Aerosol	Gloss Black	655
TRIMMB/AL	450ml Aerosol	Matt Black	655
TRIMSB/AL	450ml Aerosol	Satin Black	650
TRIMGW/AL	450ml Aerosol	Gloss White	630
TRIMSL/AL	450ml Aerosol	Silver Wheels	655
TRIMST/AL	450ml Aerosol	Steel Wheels	655

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL AUSTRALIA PTY Ltd
PO BOX 375
Springwood NSW 2777
WWW.U-POL.COM

Contact Australia
T: +61 2 4731 2655
F: +61 2 4731 2611
sales@u-pol.com.au

U-POL NEW ZEALAND Ltd
T: +64 27 630 3691
F: +61 2 4731 2611
sales@u-pol.com

Technical
T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com