



# 2K CUSTOM CAN AEROSOL

CCUP2K/AL

Version: 1.0

Date of issue: 13/07/2021 Revision date: 13/07/2021



DRIVING SURFACE PERFECTION

## TECHNICAL DATASHEET

A 2K pre-gassed Custom Can that can be filled with 100ml of a 2K solvent based topcoat. It gives a clog-free, professional, spray gun finish with the convenience of an aerosol. Provides excellent flow properties and helps extend the normal pot-life of the coating.

- Fill with 100ml of non-activated topcoat base.
- 2k durability at the touch of a button.
- Contains isocyanate activator.

<b>Product</b> 2K CUSTOM CAN AEROSOL	<b>Order Code</b> CCUP2K/AL	<b>Format</b> 400ml Aerosol	<b>Shelf Life</b> 2 years
---	--------------------------------	--------------------------------	------------------------------

## APPLICATION INFORMATION



**IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.** This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information.



### Surface Preparation



**Substrate**  
as per paint manufacturers instructions / TDS.

**Degreaser**  
WIPE #6 Solvent-Based Degreaser Aerosol

**Abrasion**

Custom Can may be applied using the preparation procedure shown below:  
 1) Degrease with Precleaner or Panel Prep and allow to dry (E.g. U-POL S2000, S2001 or S2002 Degreasers)  
 2) Abrade surface wet or dry with P400-P600 grit.  
 3) Re-clean, dry and degrease again.

### Filling



For best practice invert can and clear valve after filling.  
 Refer to the machine manual for filling instructions.  
 Fill with maximum 100ml paint.  
 Compatibility and storage stability will vary with formulation. Check the product quality before giving to the end user.

### Mixing



Activate and shake the aerosol can for at least 2 minutes before activation.



**Working Pot-Life at 20°C** 8 hours  
**Application Temperature** 20 °C  
**Coats** 2 – 3

### Drying Time



PLEASE NOTE: drying times are dependent upon film thickness, humidity and temperature. Allow to dry according to paint manufacturer recommendations.

### Polishing



**Ready to Polish at 20°C** over night

## TECHNICAL INFORMATION

### Physical properties



**Appearance** aerosol.  
**Colour** Colourless  
**Density** 0.766 g/cm<sup>3</sup>

### VOC Information



**VOC Category (2004/42/CE)** Special Finishes, product category IIB(e), max. limit 840 g/l  
 The VOC content of this product as received is 651 g/l. The VOC content of this product in ready to use form is < 840 g/l.

### Storage

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To clear the nozzle and maximise the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use. Should the nozzle become blocked, remove it from the can and soak it in gentle thinners.



# 2K CUSTOM CAN AEROSOL

CCUP2K/AL

Version: 1.0

Date of issue: 13/07/2021 Revision date: 13/07/2021



DRIVING SURFACE PERFECTION

## TECHNICAL DATASHEET



Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

**Recommended storage temperature** 5 °C - 25 °C

### Associated Products



#### Product

SYSTEM 20 Water-Based Degreaser  
 SYSTEM 20 Solvent-Based Fast Degreaser  
 SYSTEM 20 Solvent-Based Slow Degreaser  
 SYSTEM 20 Solvent-Based Slow Degreaser  
 WIPE #6 Solvent-Based Degreaser Aerosol  
 MAXIMUM Professional Lint-Free Solvent Wipes  
 MAXIMUM Tack Cloths  
 MAXIMUM Tack Cloths  
 MAXIMUM Premium Masks  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Painters Overalls  
 MAXIMUM Abrasive Latex Paper Discs P400  
 MAXIMUM Abrasive Latex Paper Discs P500  
 MAXIMUM Abrasive Latex Paper Discs P600  
 MAXIMUM Abrasive Latex Paper Discs P800

#### Order Code

S2000/5 5L Canister  
 S2001/5 5L Tin  
 S2002/1 1L Tin  
 S2002/5 5L Tin  
 WIPE/AL 450ml Aerosol  
 MWPP/350 100-pack  
 TRAG/10 10-pack  
 TRAG/50 50-pack  
 RESPV 1-pack  
 COVER/M 1-pack  
 COVER/L 1-pack  
 COVER/XL 1-pack  
 COVER/XXL 1-pack  
 COVER/XXXL 1-pack  
 ABD7/VP400 100-pack  
 ABD7/VP500 100-pack  
 ABD7/VP600 100-pack  
 ABD7/VP800 100-pack

#### Format

U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits. U-POL is not liable for mis-use or abuse of its products and no application warranty is expressed or implied.



For additional technical assistance, please contact the U-POL Technical Department at [technicalsupport@u-pol.com](mailto:technicalsupport@u-pol.com)

U-POL Australia Pty Limited  
 55 Leland Street  
 NSW 2750 Penrith - Australia  
 T 02 4731 2655 - F 02 4731 2611  
[info@u-pol.co.au](mailto:info@u-pol.co.au) - [www.u-pol.com](http://www.u-pol.com)

U-POL New Zealand Limited  
 c/o Lindsay & Associates  
 Unit H, 12 Amara Place, East Tamaki  
 2013 Manukau City - New Zealand  
 T + 612 4731 2655 - F + 612 4731 2611  
[info@u-pol.co.nz](mailto:info@u-pol.co.nz) - [www.u-pol.com](http://www.u-pol.com)