

Safety Data Sheet
 according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

1 Identification

Product Name: BRUNOX® EPOXY - SPRAY

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Coating

Details of Manufacturer or Importer:

REFINISH IMPORTS PTY LTD
 Unit A, 16 -20 Cassola Place
 Penrith, NSW 2750

Phone Number: (02) 4709 6377

Emergency telephone number: (CHEMTREC): + (61) -290372994

Email: INFO@REFINISHIMPORTSANZ.COM

2 Hazard(s) Identification

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).



Flame

Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.



Skull and crossbones

Acute Toxicity (Inhalation) 3

H331

Toxic if inhaled.



Health hazard

Carcinogenicity 2

H351

Suspected of causing cancer.



Serious Eye Damage/Irritation 2A H319

Causes serious eye irritation.

STOT SE 3

H336

May cause drowsiness or dizziness.

Signal Word Danger

Hazard Statements

H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H331 Toxic if inhaled.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

Precautionary Statements

P201 Obtain special instructions before use.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 1)

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

Additional Information AUH066 Repeated exposure may cause skin dryness or cracking.

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 67-64-1	Acetone ⚠ Flammable Liquids 2, H225; ⚠ Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H336	25 - 50%
CAS: 67-63-0	2-Propanol ⚠ Flammable Liquids 2, H225; ⚠ Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H336	2.5 - <10%
CAS: 107-98-2	1-Methoxy-2-propanol [Monopropylene glycol methyl ether] ⚠ Flammable Liquids 3, H226; ⚠ STOT SE 3, H336	2.5 - <10%
CAS: 108-10-1	2-Pentanone, 4-methyl- ⚠ Flammable Liquids 2, H225; ⚠ Carcinogenicity 2, H351; ⚠ Acute Toxicity (Inhalation) 4, H332; ⚠ Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H335	2.5 - <10%
CAS: 112-34-5	2-(2-butoxyethoxy)ethanol ⚠ Serious Eye Damage/Irritation 2A, H319	2.5 - <10%
CAS: 10024-97-2	Dinitrogen oxide ⚠ Oxidising Gases 1, H270; ⚠ Press. Gas L, H280; ⚠ Acute Toxicity (Inhalation) 1, H330	2.5 - <10%
CAS: 64-18-6	Formic acid ⚠ Skin Corrosion/Irritation 1A, H314; ⚠ Flammable Liquids 4, H227	0.1 - <2%

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 2)

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.

Ingestion:

If swallowed, do not induce vomiting. Immediately rinse mouth with water. Give a glass of water. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: Toxic if inhaled. May cause drowsiness and dizziness.

Skin Contact: No adverse health effects expected.

Eye Contact: Causes serious eye irritation.

Ingestion: No adverse health effects expected.

5 Fire Fighting Measures

Suitable Extinguishing Media: Sand, dry chemical or carbon dioxide. Do not use water.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon.

Product is extremely flammable. Vapours may travel considerable distances to a source of ignition where they can ignite, flashback, or explode.

Closed containers may explode when exposed to extreme heat. Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots.

Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation.

Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so. Remove leaking containers to a well-ventilated area and allow to discharge. Absorb spills with sand, earth, vermiculite or some other absorbent material. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Do not pierce or burn containers, even after use. Do not spray at flame or other ignition source. Do not expose to temperatures above 50 °C.

Food, beverages and tobacco products should not be stored or consumed where this material is in use.

Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 3)

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep in original container. Protect from heat, sparks, open flames and other sources of ignition. Store below 25 °C.

8 Exposure Controls and Personal Protection

Exposure Standards:**CAS: 67-64-1 Acetone**

WES	STEL: 2375 mg/m ³ , 1000 ppm TWA: 1185 mg/m ³ , 500 ppm
-----	--

CAS: 67-63-0 2-Propanol

WES	STEL: 1230 mg/m ³ , 500 ppm TWA: 983 mg/m ³ , 400 ppm
-----	--

CAS: 107-98-2 1-Methoxy-2-propanol [Monopropylene glycol methyl ether]

WES	STEL: 553 mg/m ³ , 150 ppm TWA: 369 mg/m ³ , 100 ppm
-----	---

CAS: 108-10-1 2-Pentanone, 4-methyl-

WES	STEL: 307 mg/m ³ , 75 ppm TWA: 205 mg/m ³ , 50 ppm
-----	---

CAS: 10024-97-2 Dinitrogen oxide

WES	TWA: 45 mg/m ³ , 25 ppm
-----	------------------------------------

CAS: 64-18-6 Formic acid

WES	STEL: 19 mg/m ³ , 10 ppm TWA: 9.4 mg/m ³ , 5 ppm
-----	---

Engineering Controls:

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

Respiratory Protection:

Use an approved Type AX/P2 vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Nitrile and butyl rubber gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered. Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form:	Aerosol
Colour:	Amber coloured
Odour:	Characteristic

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 4)

Odour Threshold:	No information available
pH-Value at 20 °C:	4.8
Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	55 °C
Flash Point:	13 °C
Flammability:	Extremely flammable
Ignition Temperature	270 °C
Auto-ignition Temperature:	Product is not self-igniting.
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	2.6 Vol %
Upper:	13 Vol %
Vapour Pressure at 20 °C:	233 hPa
Density at 20 °C:	0.93 g/cm ³
Relative Density:	No information available
Vapour Density:	No information available
Evaporation Rate:	Not applicable
Solubility in Water:	Immiscible
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	No information available
Solvent separation test:	
VOC:	65.47 %

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of storage and use.

Conditions to Avoid: Heat, sparks, open flames and other sources of ignition.

Incompatible Materials: No further relevant information available.

Hazardous Decomposition Products: Oxides of carbon.

11 Toxicological Information

Toxicity:

LD50/LC50 Values Relevant for Classification:

CAS: 67-64-1 Acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	>7,426 mg/kg (rabbit)
Inhalation	LC50/4 h	30,000 ppm (rat)

CAS: 67-63-0 2-Propanol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalation	LC50/4 h	30 mg/l (rat)

CAS: 107-98-2 1-Methoxy-2-propanol [Monopropylene glycol methyl ether]

Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)

CAS: 108-10-1 2-Pentanone, 4-methyl-

Oral	LD50	2,080 mg/kg (rat)
------	------	-------------------

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 5)

Dermal	LD50	16,000 mg/kg (rabbit)
Inhalation	LC50/4 h	8.3-16.6 mg/l (rat)
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	4,000 mg/kg (rabbit)
CAS: 10024-97-2 Dinitrogen oxide		
Inhalation	LC50/4 h	1.06 mg/l (rat)
CAS: 64-18-6 Formic acid		
Oral	LD50	1,100 mg/kg (rat)

Acute Health Effects**Inhalation:** Toxic if inhaled. May cause drowsiness and dizziness.**Skin:** No adverse health effects expected.**Eye:** Causes serious eye irritation.**Ingestion:** No adverse health effects expected.**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Suspected of causing cancer.

Methyl isobutyl ketone is classified by IARC as Group 2B - Possibly carcinogenic to humans.

Isopropyl alcohol is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause drowsiness and dizziness.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** Repeated exposure may cause skin dryness or cracking.**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available**12 Ecological Information****Ecotoxicity:****Aquatic toxicity:****CAS: 67-64-1 Acetone**

EC50/48 h 12,600 mg/l (daphnia)

LC50/96 h 4,740-6,330 mg/l (rainbow trout)

CAS: 67-63-0 2-Propanol

EC50/48 h 100 mg/l (daphnia)

EC50/72 h 100 mg/l (scenedesmus subspicatus)

LC50/96 h 1,400 mg/l (bluegill)

9,640 mg/l (fathead minnow)

(Contd. on page 7)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 6)

LC50/48 h	8,970 mg/l (golden orfe)
CAS: 107-98-2 1-Methoxy-2-propanol [Monopropylene glycol methyl ether]	
EC50/48 h	500 mg/l (daphnia)
EC50/72 h	1,000 mg/l (selenastrum capricornutum)
LC50/96 h	1,000 mg/l (rainbow trout)
CAS: 108-10-1 2-Pentanone, 4-methyl-	
EC50/48 h	170 mg/l (daphnia)
EC50/96 h	400 mg/l (selenastrum capricornutum)
LC50/96 h	600 mg/l (rainbow trout)
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
EC50	>100 mg/l (algae)
EC50/48 h	>100 mg/l (daphnia)
LC50/96 h	1,300 mg/l (lepomis macrochirus)
LC50	>100 mg/l (golden orfe)

Persistence and Degradability: No further relevant information available.**Bioaccumulative Potential:** No further relevant information available.**Mobility in Soil:** No further relevant information available.**Other adverse effects:**

Classified as Water Hazard Class 1 according to the German Regulations - Slightly hazardous for water.

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number	
ADG, IMDG, IATA	UN1950
Proper Shipping Name	
ADG, IMDG, IATA	AEROSOLS
Dangerous Goods Class	
ADG Class:	2.1
Subsidiary Risk:	
Packing Group:	Not applicable
Marine pollutant:	
EMS Number:	F-D,S-U
Special Provisions:	63, 190, 277, 327, 344, 381
Transport/Additional information:	
Limited Quantities:	1L
Packagings & IBCs - Packing Instruction:	P207, LP200

(Contd. on page 8)

Safety Data Sheet

according to WHS Regulations

Printing date 14.05.2021

Revision: 14.05.2021

Product Name: BRUNOX® EPOXY - SPRAY

(Contd. of page 7)

Packagings & IBCs - Special Packing Provisions: PP87, L2

15 Regulatory Information

Australian Inventory of Industrial Chemicals:

All ingredients are listed.

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Poison Schedule:

Poisons Schedule: 5

16 Other Information

Date of Preparation or Last Revision: 18.08.2020**Prepared by:** MSDS.COM.AU Pty Ltdwww.msds.com.au**Abbreviations and acronyms:**

ADG: Australian Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Aerosol 1: Aerosols – Category 1

Oxidising Gases 1: Oxidising gases, Hazard Category 1

Press. Gas L: Gases under pressure – Liquefied gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 3: Flammable liquids – Category 3

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity (Inhalation) 1: Acute toxicity - inhalation – Category 1

Acute Toxicity (Inhalation) 3: Acute toxicity - inhalation – Category 3

Acute Toxicity (Inhalation) 4: Acute toxicity - inhalation – Category 4

Skin Corrosion/Irritation 1A: Skin corrosion/irritation – Category 1A

Serious Eye Damage/Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document “Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - July 2020”

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. REFINISH IMPORTS PTY LTD makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.