

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : SMCW  
**Product name** : SMC CARBON FIBRE REINFORCED FILLER - WHITE  
**Other means of identification** : SMCW/2  
**Date of issue** : 4 March 2024  
**Version** : 1.01

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Putty.  
**Uses advised against** : Not for sale to or use by consumers.

**Supplier's details** : U-POL Australia Pty Ltd. OFFICE: UNIT 8  
55 Leland Street, Penrith, NSW 2750  
PO BOX 324, ROZELLE NSW 2039  
Australia  
02 4731 2655  
info@u-pol.com.au  
A.C.N. 633 592 819  
U-POL New Zealand Limited Ltd  
Importer: Lindsay & Associates  
Unit H 12 Amera Place, East Tamaki  
Auckland, New Zealand  
027 630 3691 / + 612 4731 2655  
info@u-pol.co.nz

**Product information** : (855) 6-AXALTA

**Emergency telephone number** : Australia (CHEMTREC): + (61) - 290372994  
New Zealand (National Poisons Centre): 0800 764 766

### Section 2. Hazard(s) identification

Classified as **HAZARDOUS** according to the GHS criteria under Australian Work Health Safety (WHS) Act 2011.

Not classified as **DANGEROUS GOODS** according to the Australian Dangerous Goods (ADG).

**Classification of the substance or mixture** : SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A  
GERM CELL MUTAGENICITY - Category 2  
REPRODUCTIVE TOXICITY - Category 2  
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1

#### GHS label elements

**Hazard pictograms** :



**Signal word** : **DANGER**

## Section 2. Hazard(s) identification

**Hazard statements** : H315 - Causes skin irritation.  
 H319 - Causes serious eye irritation.  
 H341 - Suspected of causing genetic defects.  
 H361 - Suspected of damaging fertility or the unborn child.  
 H372 - Causes damage to organs through prolonged or repeated exposure.  
 (hearing organs)

### Precautionary statements

**Prevention** : P201 - Obtain special instructions before use.  
 P260 - Do not breathe dust.  
 P270 - Do not eat, drink or smoke when using this product.  
 P264 - Wash hands thoroughly after handling.  
 P280 - Wear protective gloves, protective clothing and eye or face protection.

**Response** : P308 + P313 - IF exposed or concerned: Get medical advice or attention.  
 P362 + P364 - Take off contaminated clothing and wash it before reuse.  
 P302 + P352 - IF ON SKIN: Wash with plenty of water.  
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing.  
 P337 + P313 - If eye irritation persists: Get medical advice or attention.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Supplemental label elements** : Not applicable.

**Other hazards which do not result in classification** : None known.

## Section 3. Composition and ingredient information

**Substance/mixture** : Mixture

| Ingredient name                          | % (w/w)  | CAS number  |
|--|----------|-------------|
| Limestone                                | 30 - <60 | 1317-65-3   |
| Talc , not containing asbestiform fibres | 10 - <30 | 14807-96-6  |
| styrene                                  | 10 - <30 | 100-42-5    |
| glass, oxide, chemicals                  | 1 - <3   | 65997-17-3  |
| Silica, amorphous, fumed, cryst.-free    | 1 - <3   | 112945-52-5 |
| titanium dioxide                         | 1 - <3   | 13463-67-7  |

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

**The total concentration of ingredients in this product, reported or not in this section, is 100%.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

## Section 4. First aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## Section 4. First aid measures

See toxicological information (Section 11)

## Section 5. Firefighting measures

### Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing media** : None known.

**Specific hazards arising from the chemical** : No specific fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** : Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

**Large spill** : Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls and personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                          | Exposure limits   |
|--|---|
| Limestone                                | <p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [calcium carbonate]</b><br/>                     TWA: 4 mg/m<sup>3</sup> 8 hours. Form: respirable dust<br/>                     TWA: 10 mg/m<sup>3</sup> 8 hours. Form: inhalable dust</p> <p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [limestone]</b><br/>                     TWA: 4 mg/m<sup>3</sup> 8 hours. Form: respirable<br/>                     TWA: 10 mg/m<sup>3</sup> 8 hours. Form: total inhalable</p> |
| Talc , not containing asbestiform fibres | <p><b>Safe Work Australia (Australia, 10/2022).</b><br/>                     TWA: 2.5 mg/m<sup>3</sup> 8 hours.</p>   |
| styrene                                  | <p><b>Safe Work Australia (Australia, 10/2022).</b><br/>                     STEL: 426 mg/m<sup>3</sup> 15 minutes.<br/>                     STEL: 100 ppm 15 minutes.<br/>                     TWA: 213 mg/m<sup>3</sup> 8 hours.<br/>                     TWA: 50 ppm 8 hours.</p>  |
| glass, oxide, chemicals                  | <p><b>ACGIH TLV (United States, 1/2023). [Continuous filament glass fibers]</b><br/>                     TWA: 5 mg/m<sup>3</sup> 8 hours. Form: Inhalable fraction<br/>                     TWA: 1 f/cc 8 hours. Form: Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.</p>   |
| Silica, amorphous, fumed, cryst.-free    | <p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020). [silica, amorphous]</b></p>   |

## Section 8. Exposure controls and personal protection

titanium dioxide

TWA: 2.4 mg/m<sup>3</sup> 8 hours. Form: respirable dust  
 TWA: 6 mg/m<sup>3</sup> 8 hours. Form: inhalable dust  
**Safe Work Australia (Australia, 10/2022).**  
 TWA: 10 mg/m<sup>3</sup> 8 hours.

### Biological exposure indices

No exposure indices known.

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

|   |  |
|---|--|
| <b>Physical state</b>                               | : Solid.   |
| <b>Colour</b>                                       | : White.   |
| <b>Odour</b>  | : Not available.   |
| <b>Odour threshold</b>                              | : Not available.   |
| <b>pH</b>   | : Not applicable.  |
| <b>Melting point</b>                                | : Technically not possible to measure                                |
| <b>Boiling point</b>                                | : Not applicable.  |
| <b>Flash point</b>                                  | : Closed cup: Not applicable. [Product does not sustain combustion.] |
| <b>Evaporation rate</b>                             | : Not available.   |
| <b>Flammability (solid, gas)</b>                    | : Not available.   |
| <b>Lower and upper explosive (flammable) limits</b> | : Not available.   |
| <b>Vapour pressure</b>                              | : 0.093 kPa (0.7 mm Hg)  |
| <b>Vapour density</b>                               | : Not applicable.  |
| <b>Density</b>                                      | : 1.865 g/cm <sup>3</sup>  |
| <b>Solubility(ies)</b>                              | :<br>Not available.  |
| <b>Partition coefficient: n-octanol/water</b>       | : Not applicable.  |
| <b>Auto-ignition temperature</b>                    | : 490°C (914°F)  |
| <b>Decomposition temperature</b>                    | : Not applicable.  |
| <b>Viscosity</b>                                    | : Not applicable.  |
| <b>Flow time (ISO 2431)</b>                         | : Not available.   |

## Section 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>Chemical stability</b>                 | : The product is stable.   |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>Conditions to avoid</b>                | : No specific data.  |
| <b>Incompatible materials</b>             | : No specific data.  |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name               | Result                 | Species | Dose                    | Exposure |
|---------------------------------------|------------------------|---------|-------------------------|----------|
| Limestone styrene                     | LD50 Oral              | Rat     | 6450 mg/kg              | -        |
|                                       | LC50 Inhalation Gas.   | Rat     | 2770 ppm                | 4 hours  |
|                                       | LC50 Inhalation Vapour | Rat     | 11800 mg/m <sup>3</sup> | 4 hours  |
| Silica, amorphous, fumed, cryst.-free | LD50 Oral              | Rat     | 2650 mg/kg              | -        |
|                                       | LD50 Oral              | Rat     | 3160 mg/kg              | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| styrene                 | Eyes - Mild irritant     | Human   | -     | 50 ppm          | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 mg | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 mg          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 500 mg          | -           |
|                         | Skin - Moderate irritant | Rabbit  | -     | 100 %           | -           |

#### Sensitisation

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

| Name    | Category   | Route of exposure | Target organs                |
|---------|------------|-------------------|------------------------------|
| styrene | Category 3 | -                 | Respiratory tract irritation |

#### Specific target organ toxicity (repeated exposure)

| Name    | Category   | Route of exposure | Target organs  |
|---------|------------|-------------------|----------------|
| styrene | Category 1 | -                 | hearing organs |

#### Aspiration hazard

Not available.

Information on likely routes of exposure : Not available.

#### Potential acute health effects

## Section 11. Toxicological information

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | : Causes serious eye irritation.                    |
| <b>Inhalation</b>   | : No known significant effects or critical hazards. |
| <b>Skin contact</b> | : Causes skin irritation.                           |
| <b>Ingestion</b>    | : No known significant effects or critical hazards. |

### Symptoms related to the physical, chemical and toxicological characteristics

|                     |  |
|---------------------|--|
| <b>Eye contact</b>  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness   |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>redness<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations |
| <b>Ingestion</b>    | : Adverse symptoms may include the following:<br>reduced foetal weight<br>increase in foetal deaths<br>skeletal malformations                          |

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### Long term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### Potential chronic health effects

Not available.

|                              |   |
|------------------------------|---|
| <b>General</b>               | : Causes damage to organs through prolonged or repeated exposure. |
| <b>Carcinogenicity</b>       | : No known significant effects or critical hazards.               |
| <b>Mutagenicity</b>          | : Suspected of causing genetic defects.                           |
| <b>Teratogenicity</b>        | : Suspected of damaging the unborn child.                         |
| <b>Developmental effects</b> | : No known significant effects or critical hazards.               |
| <b>Fertility effects</b>     | : No known significant effects or critical hazards.               |

### Numerical measures of toxicity

#### Acute toxicity estimates

## Section 11. Toxicological information

| Route                | ATE value    |
|----------------------|--------------|
| Inhalation (gases)   | 27518.46 ppm |
| Inhalation (vapours) | 117.23 mg/l  |

## Section 12. Ecological information

### Toxicity

| Product/ingredient name | Result                                | Species                             | Exposure |
|-------------------------|---------------------------------------|-------------------------------------|----------|
| styrene                 | Acute EC50 78000 µg/l Marine water    | Algae - <i>Skeletonema costatum</i> | 96 hours |
|                         | Acute LC50 52 mg/l Marine water       | Crustaceans - <i>Artemia salina</i> | 48 hours |
|                         | Acute LC50 23 mg/l Fresh water        | Daphnia - <i>Daphnia magna</i>      | 48 hours |
| titanium dioxide        | Acute LC50 >1000000 µg/l Marine water | Fish - <i>Fundulus heteroclitus</i> | 96 hours |

### Persistence and degradability

Not available.

### Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF   | Potential |
|-------------------------|--------------------|-------|-----------|
| styrene                 | 0.35               | 13.49 | Low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                            | ADG            | IMDG           | IATA           |
|----------------------------|----------------|----------------|----------------|
| UN number                  | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name    | -              | -              | -              |
| Transport hazard class(es) | -              | -              | -              |
| Packing group              | -              | -              | -              |
| Environmental hazards      | No.            | No.            | No.            |

### Additional information

Hazchem code : Not available.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

### Model Work Health and Safety Regulations - Scheduled Substances

| Ingredient name                    | Schedule  |
|------------------------------------|---|
| crystalline silica, non-respirable | Restricted hazardous chemical [For abrasive blasting at a concentration of greater than 1%] |

## Section 16. Any other relevant information

### History

**Date of issue** : 4 March 2024

**Key to abbreviations** :

- ACGIH = Association Advancing Occupational and Environmental Health
- ADG = Australian Dangerous Goods
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- DFG = Deutsche Forschungsgemeinschaft, German research funding organization
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MAK value = Maximum Permissible Concentration

## Section 16. Any other relevant information

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

STEL = Short-Term Exposure Limit

TLV = Threshold Limit Value

TWA = Time-Weighted Average

✔ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.